## NSN 4720-01-112-3684

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-112-3684

Cross Sectional Shape:					
Round					
Thread Class:					
2b 1st end					
Thread Direction:					
Right-hand 1st end					
Inside Diameter:					
0.625 inches					
Tempurature Rating:					
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response					
Outside Diameter:					
0.971 inches					
Minimum Inside Bending Radius:					
8.000 inches					
Exterior Color:					
Black					
Connection Style:					
Swivel nut flare 1st end					
End Connection Design:					
Straight 1st end					
Connection Type:					
Threaded internal tube 1st end					
Thready Qty Per Inch (tpi):					
12 1st end					
Burst Test Pressure:					
6000.0 pounds per square inch					
Layer Composition And Location:					
1st layer braided wire and outer layer molded rubber, synthetic					
Maximum Operating Pressure:					
1500.0 pounds per square inch					
Thread Size:					
1.062 inches 1st end					
Seat Angle:					
37.0 degrees 1st end					
Hydrostatic Test Pressure:					
3000.0 pounds per square inch					
Outer Covering Environmental Protection:					
Oil resistant and weatherproof					
Inside Surface Condition:					
Smooth					
Measuring Method And Length:					

84.000 inches

## NSN 4720-01-112-3684

Nonmetallic Hose Assembly - Page 2 of 2



	Media	For	Which	Design	ned:
--	-------	-----	-------	--------	------

Hydraulic fluid single response

**Thread Series Designator:** 

Un 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0