Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-113-8307

Cross Sectional Shape:	
0.000 000.000 0.00 por	
Round	
Inside Diameter:	
0.250 inches	
Tempurature Rating:	
-65.0 degrees fahrenheit and 160.0 degre	es fahrenheit single response
Outside Diameter:	
0.703 inches	
Minimum Inside Bending Radius:	
3.500 inches	
Burst Test Pressure:	
16000.0 pounds per square inch	
Layer Composition And Location:	
1st layer braided corrosion resistant steel	wire or 1st layer spirally wrapped corrosion resistant steel fabric and 2nd layer braided corrosion
resistant steel wire or 2nd layer spirally w	rapped corrosion resistant steel fabric and outer layer molded rubber, chloroprene
Maximum Operating Pressure:	
4000.0 pounds per square inch	
Hydrostatic Test Pressure:	
8000.0 pounds per square inch	
Outer Covering Environmental Protection	on:
Abrasion resistant and oil resistant and oz	one resistant
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
11.000 inches	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A542a0	