NSN 4720-01-114-6936

Non-conductive hose

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-114-6936

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response
Outside Diameter:
0.570 inches
Minimum Inside Bending Radius:
0.750 inches
Exterior Color:
Green
Connection Style:
Swivel nut, flareless 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
800.0 pounds per square inch
Layer Composition And Location:
Outer layer braided polyamide cord
Maximum Operating Pressure:
200.0 pounds per square inch
Thread Size:
0.562 inches 2nd end
Seat Angle:
12.0 degrees 2nd end
Hydrostatic Test Pressure:
300.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Inside Surface Condition:
Convoluted
Measuring Method And Length:
30.000 inches
Special Features:

NSN 4720-01-114-6936

Nonmetallic Hose Assembly - Page 2 of 2



Thread	Series	Design	nator:
	0000	_00.9.	

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0