

View Online at <https://aerobasegroup.com/nsn/4720-01-115-1391>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.500 inches

**Temperature Rating:**

-40.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response

**Outside Diameter:**

0.920 inches

**Minimum Inside Bending Radius:**

5.500 inches

**Exterior Color:**

Black

**Hose Or Tubing Specification/std Data:**

Sae j517, 100r5, size 10-81343 standard (includes industry or association standards, individual manufactureer standards, etc.).

**End Connection Design:**

Straight 1st end

**End Fitting Component And Material:**

Complete fitting steel all ends

**Fitting Component And Surface Treatment:**

Complete fitting cadmium 1st end

**Connection Type:**

Threaded internal tube 1st end

**Features Provided:**

Reusable end fittings

**Second End Relationship With First End:**

Identical

**Burst Test Pressure:**

7000.0 pounds per square inch

**First End Swivel Action Capability:**

Not included

**Layer Composition And Location:**

1st layer braided textile yarn err-100

**Maximum Operating Pressure:**

1750.0 pounds per square inch

**Thread Size:**

0.875 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Hydrostatic Test Pressure:**

3500.0 pounds per square inch

**Outer Covering Environmental Protection:**

Hydraulic solution resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

23.000 inches

**Special Features:**

Inner conveying tube material-rubber, synthetic

**Media For Which Designed:**

Hydraulic fluid single response

**Thread Series Designator:**

Unf 1st end

**Specification Data:**

Sae j517, 100r5, size 10-81343 national std/spec

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0