Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-117-2798

Round

**Thread Class:** 

3b 1st end

# Thread Direction:

Right-hand 1st end

## Inside Diameter:

0.188 inches

#### **Tempurature Rating:**

-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response

#### **Outside Diameter:**

0.312 inches

Minimum Inside Bending Radius:

2.000 inches

#### **Exterior Color:**

Natural

### **Connection Style:**

Swivel nut flare 1st end

### End Connection Design:

Straight 1st end

## Connection Type:

Threaded internal tube 1st end

## **Features Provided:**

Electrostatic discharge capability

### **Burst Test Pressure:**

12000.0 pounds per square inch

### Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

### Maximum Operating Pressure:

1500.0 pounds per square inch

#### Thread Size:

0.438 inches 1st end

### Seat Angle:

37.0 degrees 1st end

### Hydrostatic Test Pressure:

3000.0 pounds per square inch

### **Outer Covering Environmental Protection:**

Corrosion resistant

Vacuum In Torr:

50.8

### Inside Surface Condition:

Smooth

Nonmetallic Hose Assembly - Page 2 of 2



## Measuring Method And Length:

16.750 inches working

## **Thread Series Designator:**

Unf 1st end

**Specification Data:** 

96906-ms8005 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0