

View Online at <https://aerobasegroup.com/nsn/4720-01-117-9331>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.125 inches

Temperature Rating:

-40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response

Flange Thickness:

0.425 inches 2nd end

Outside Diameter:

0.435 inches

Minimum Inside Bending Radius:

2.000 inches

Exterior Color:

Black

Hose Or Tubing Specification/std Data:

Sae j1401-81343 standard (includes industry or association standards, individual manufactureer standards, etc.).

Connection Style:

Inverted flare 1st end

Bolt Hole Diameter:

0.438 inches 2nd end

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Complete fitting steel 2nd end

Fitting Component And Surface Treatment:

Complete fitting dichromate 1st end

Connection Type:

Unthreaded fluid passage bolt 2nd end

Second End Relationship With First End:

Not identical

Burst Test Pressure:

5000.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

Outer layer molded rubber, synthetic err-100

Maximum Operating Pressure:

1250.0 pounds per square inch

Thread Size:

0.375 inches 1st end

Seat Angle:

12.0 degrees 1st end

Hydrostatic Test Pressure:

2500.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

11.750 inches

Special Features:

First end furnished w/a flat mtg plate 1.882 in. Lg 1.556 in. W 0.105 in. Thk, w/one 0.282 in. Unthd mtg hole

Media For Which Designed:

Hydraulic fluid single response

Thread Series Designator:

Unf 1st end

Specification Data:

Sae j1401-81343 national std/spec

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0