NSN 4720-01-119-5208

Cross Sectional Shape:

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-119-5208

Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.785 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response
Outside Diameter:
1.075 inches
Minimum Inside Bending Radius:
3.750 inches
Exterior Color:
Natural
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Nuts drilled for lockwire
Thready Qty Per Inch (tpi):
12 1st end
12 1st end
12 1st end Burst Test Pressure:
12 1st end Burst Test Pressure: 2600.0 pounds per square inch
12 1st end Burst Test Pressure: 2600.0 pounds per square inch Layer Composition And Location:
12 1st end Burst Test Pressure: 2600.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire
12 1st end Burst Test Pressure: 2600.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure:
12 1st end Burst Test Pressure: 2600.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 650.0 pounds per square inch
12 1st end Burst Test Pressure: 2600.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 650.0 pounds per square inch Thread Size:
12 1st end Burst Test Pressure: 2600.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 650.0 pounds per square inch Thread Size: 1.062 inches 1st end
12 1st end Burst Test Pressure: 2600.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 650.0 pounds per square inch Thread Size: 1.062 inches 1st end Seat Angle:
12 1st end Burst Test Pressure: 2600.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 650.0 pounds per square inch Thread Size: 1.062 inches 1st end Seat Angle: 37.0 degrees 2nd end
Burst Test Pressure: 2600.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 650.0 pounds per square inch Thread Size: 1.062 inches 1st end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure:
Burst Test Pressure: 2600.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 650.0 pounds per square inch Thread Size: 1.062 inches 1st end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 1300.0 pounds per square inch
12 1st end Burst Test Pressure: 2600.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 650.0 pounds per square inch Thread Size: 1.062 inches 1st end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 1300.0 pounds per square inch Outer Covering Environmental Protection:

NSN 4720-01-119-5208

Nonmetallic Hose Assembly - Page 2 of 2



inside Surface Condition:
Convoluted
Measuring Method And Length:
21.000 inches working
Thread Series Designator:
Unf 2nd end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A542a0