

View Online at <https://aerobasegroup.com/nsn/4720-01-119-8835>

**Cross Sectional Shape:**

Round

**Thread Class:**

2a 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.375 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

**Outside Diameter:**

0.775 inches

**Minimum Inside Bending Radius:**

4.000 inches

**Exterior Color:**

Black

**Angle Between Rigid Elbow Fittings In Deg:**

180.0

**Connection Style:**

Swivel, plain 2nd end

**End Connection Design:**

Elbow 2nd end

**Connection Type:**

Threaded external hose 2nd end

**Thready Qty Per Inch (tpi):**

16 2nd end

**Burst Test Pressure:**

6000.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided fiber and 2nd layer braided fiber and outer layer molded rubber, synthetic

**Maximum Operating Pressure:**

1500.0 pounds per square inch

**Thread Size:**

0.687 inches 1st end

**Hydrostatic Test Pressure:**

3000.0 pounds per square inch

**Flow Angle:**

90.0 degrees 2nd end

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

28.000 inches working

**Special Features:**

First end has a steel tube 15.500 in. Lg w/two 90 degrees bends, second end has a steel tube 7.000 in. Lg w/two 90 degrees bends

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Thread Series Designator:**

Un 2nd end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0