

View Online at <https://aerobasegroup.com/nsn/4720-01-119-8835>

Cross Sectional Shape:

Round

Thread Class:

2a 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.375 inches

Temperature Rating:

-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Outside Diameter:

0.775 inches

Minimum Inside Bending Radius:

4.000 inches

Exterior Color:

Black

Angle Between Rigid Elbow Fittings In Deg:

180.0

Connection Style:

Swivel, plain 2nd end

End Connection Design:

Elbow 2nd end

Connection Type:

Threaded external hose 2nd end

Thready Qty Per Inch (tpi):

16 2nd end

Burst Test Pressure:

6000.0 pounds per square inch

Layer Composition And Location:

1st layer braided fiber and 2nd layer braided fiber and outer layer molded rubber, synthetic

Maximum Operating Pressure:

1500.0 pounds per square inch

Thread Size:

0.687 inches 1st end

Hydrostatic Test Pressure:

3000.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Inside Surface Condition:

Smooth

Measuring Method And Length:

28.000 inches working

Special Features:

First end has a steel tube 15.500 in. Lg w/two 90 degrees bends, second end has a steel tube 7.000 in. Lg w/two 90 degrees bends

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Un 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0