NSN 4720-01-119-8836

Cross Sectional Shape:

Round

Thread Class: 2b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:

Tempurature Rating:

Between 0.359 inches and 0.391 inches

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-119-8836

-65.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response
Outside Diameter:
Between 0.750 inches and 0.812 inches
Minimum Inside Bending Radius:
7.000 inches
Exterior Color:
Black
End Application:
2350-00-115-4418
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
9000.0 pounds per square inch
Maximum Operating Pressure:
2250.0 pounds per square inch
2250.0 pounds per square inch Thread Size:
Thread Size:
Thread Size: 0.562 inches 2nd end
Thread Size: 0.562 inches 2nd end Seat Angle:
Thread Size: 0.562 inches 2nd end Seat Angle: 37.0 degrees 2nd end
Thread Size: 0.562 inches 2nd end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure:
Thread Size: 0.562 inches 2nd end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 4500.0 pounds per square inch
Thread Size: 0.562 inches 2nd end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 4500.0 pounds per square inch Flow Angle:
Thread Size: 0.562 inches 2nd end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 4500.0 pounds per square inch Flow Angle: 90.0 degrees 2nd end
Thread Size: 0.562 inches 2nd end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 4500.0 pounds per square inch Flow Angle: 90.0 degrees 2nd end Outer Covering Environmental Protection:
Thread Size: 0.562 inches 2nd end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 4500.0 pounds per square inch Flow Angle: 90.0 degrees 2nd end Outer Covering Environmental Protection: Abrasion resistant
Thread Size: 0.562 inches 2nd end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 4500.0 pounds per square inch Flow Angle: 90.0 degrees 2nd end Outer Covering Environmental Protection: Abrasion resistant Inside Surface Condition:
Thread Size: 0.562 inches 2nd end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 4500.0 pounds per square inch Flow Angle: 90.0 degrees 2nd end Outer Covering Environmental Protection: Abrasion resistant Inside Surface Condition: Smooth

NSN 4720-01-119-8836

Nonmetallic Hose Assembly - Page 2 of 2



Media For Which Designe	Which Designe	ed
-------------------------	---------------	----

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0