Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-120-8517

Cross Sectional Shape:	
Round	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
Between 1.235 inches and 1.297 inches	
Tempurature Rating:	
-67.0 degrees fahrenheit and 250.0 degrees fahrenheit single response	
Outside Diameter:	
Between 1.750 inches and 1.874 inches	
Minimum Inside Bending Radius:	
16.000 inches	
Connection Style:	
Inverted flare 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded external pipe 1st end	
Burst Test Pressure:	
2500.0 pounds per square inch	
Layer Composition And Location:	
1st layer braided steel wire and outer layer molded rubber, chloroprene	
Maximum Operating Pressure:	
625.0 pounds per square inch	
Thread Size:	
1.250 inches 1st end	
Seat Angle:	
30.0 degrees 1st end	
Hydrostatic Test Pressure:	
1250.0 pounds per square inch	
Outer Covering Environmental Protection:	
Cold resistant and mildew resistant and oil resistant and ozone resistant	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
127.070 inches and 28.030 inches	
Media For Which Designed:	
Fuel/oil, hydrocarbon single response	
Thread Series Designator:	
Nptf 1st end	
Shelf Life:	
N/a	

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0