

View Online at <https://aerobasegroup.com/nsn/4720-01-121-0638>

Cross Sectional Shape:

Round

Inside Diameter:

3.000 inches

Tempurature Rating:

250.0 degrees fahrenheit single response

Bolt Circle Diameter:

6.000 inches 1st end

Flange Thickness:

0.688 inches 1st end

Outside Diameter:

3.500 inches

Inner Conveying Tube Style:

Annular close-pitch corrugated

Exterior Color:

Natural

Bolt Hole Quantity:

4 1st end

Flange Outside Diameter:

7.500 inches 1st end

End Application:

Ships service generator onboard 270 ft wmec coast guard vessels

Connection Style:

Plain 1st end

Bolt Hole Diameter:

0.625 inches 1st end

End Flange Construction:

Solid 1st end

End Connection Design:

Straight 1st end

Connection Type:

Plain face flange 1st end

Features Provided:

Identical ends

Burst Test Pressure:

250.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

15.0 pounds per square inch

Measuring Method And Length:

17.500 inches

Flange Style:

Round w/ bolt holes 1st end

Special Features:

Pipe size 3 in; live length 13 in; test pressure 250 psi; lateral motion 1 in; flex connection for stainless steel generator jacket water piping tap front of engine to waste heat recovery unit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0