

View Online at <https://aerobasegroup.com/nsn/4720-01-121-0869>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.520 inches

Temperature Rating:

-65.0 degrees fahrenheit and 400.0 degrees fahrenheit single response

Outside Diameter:

0.755 inches

Minimum Inside Bending Radius:

2.880 inches

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Burst Test Pressure:

4000.0 pounds per square inch

Layer Composition And Location:

1st layer polytetrafluoroethylene impregnated glass fiber and outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

1000.0 pounds per square inch

Thread Size:

0.750 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

2000.0 pounds per square inch

Vacuum In Torr:

50.8

Inside Surface Condition:

Convuluted

Measuring Method And Length:

60.000 inches working

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0