

View Online at <https://aerobasegroup.com/nsn/4720-01-121-6689>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.406 inches

Temperature Rating:

-65.0 degrees fahrenheit and 450.0 degrees fahrenheit single response

Outside Diameter:

0.562 inches

Connection Style:

Swivel nut, flareless 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Burst Test Pressure:

8000.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

1500.0 pounds per square inch

Thread Size:

0.750 inches 1st end

Seat Angle:

24.0 degrees 1st end

Hydrostatic Test Pressure:

3000.0 pounds per square inch

Outer Covering Environmental Protection:

Fire resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

13.000 inches working

Supplementary Features:

This item has been reviewed for asbestos material. The current approved sources (rnvc 2) have indicated their part number contained asbestos. They continue to manufacture the same part number without asbestos material

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0