## NSN 4720-01-122-8195

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-122-8195

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.500 inches
Minimum Inside Bending Radius:
2.000 inches
Exterior Color:
Black
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
20000.0 pounds per square inch
Layer Composition And Location:
1st layer braided fiber and outer layer molded rubber, ethylene propylene
Maximum Operating Pressure:
5000.0 pounds per square inch
Thread Size:
0.562 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
10000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
387.000 inches
Thread Series Designator:
Unf 1st end
Shelf Life:
N/a

## NSN 4720-01-122-8195

Nonmetallic Hose Assembly - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A542a0