Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-122-9155

С	ross Sectional Shape:
R	ound
т	hread Class:
3	b 1st end
т	hread Direction:
R	ight-hand 1st end
Ir	side Diameter:
0	875 inches
Т	empurature Rating:
-4	10.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response
0	utside Diameter:
1	.500 inches
N	linimum Inside Bending Radius:
9	.625 inches
Е	xterior Color:
В	lack
С	onnection Style:
G	asket seal / optional end 1st end
Е	nd Connection Design:
s	traight 1st end
С	onnection Type:
т	hreaded internal boss 1st end
в	urst Test Pressure:
1	0000.0 pounds per square inch
N	laximum Operating Pressure:
3	000.0 pounds per square inch
т	hread Size:
1	500 inches 1st end
Ir	side Surface Condition:
S	mooth
N	leasuring Method And Length:
3	60.000 inches working
N	ledia For Which Designed:
Н	ydraulic fluid single response
т	hread Series Designator:
U	nf 1st end
S	helf Life:
Ν	/a
U	nit Of Measure:
D	emilitarization:
Ν	0

NSN 4720-01-122-9155

Nonmetallic Hose Assembly - Page 2 of 2

Fiig: A542a0

