NSN 4720-01-123-1526

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-123-1526

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.173 inches
Tempurature Rating:
-67.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
0.343 inches
Minimum Inside Bending Radius:
2.000 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
12000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.4375 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Vacuum In Torr:
50.8
Inside Surface Condition:
Smooth
Measuring Method And Length:
22.000 inches
Special Features:
Grumman aircraft f18

NSN 4720-01-123-1526

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:
Unf 1st end
Specification Data:
96906-ms8005a government specification
Specification Or Standard:
1 class
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A542a0