

View Online at <https://aerobasegroup.com/nsn/4720-01-123-5010>

Cross Sectional Shape:

Round

Inside Diameter:

1.181 inches

Temperature Rating:

-40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response

Bolt Circle Diameter:

3.940 inches 1st end

Flange Thickness:

0.440 inches 1st end

Outside Diameter:

2.220 inches

Minimum Inside Bending Radius:

13.250 inches

Bolt Hole Quantity:

6 1st end

Flange Outside Diameter:

5.060 inches 1st end

Connection Style:

Raised swivel 1st end

Bolt Hole Diameter:

0.560 inches 1st end

Raised Face Height:

0.010 inches 1st end and 0.020 inches 1st end

Raised Face Diameter:

2.740 inches 1st end

End Flange Construction:

Solid 1st end

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Socket nickel alloy 2nd end

Connection Type:

Raised face flange 1st end

Second End Relationship With First End:

Identical

Burst Test Pressure:

1400.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

Outer layer molded rubber, synthetic err-100

Maximum Operating Pressure:

350.0 pounds per square inch

Hydrostatic Test Pressure:

700.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

47.000 inches

Flange Style:

Round w/ bolt holes 1st end

Special Features:

Two hose assembly connected by 90 degrees elbow, first leg lg 26.000, second leg lg 21.000

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0