## NSN 4720-01-123-8830

**Cross Sectional Shape:** 

Round

Thread Class: 3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-123-8830

| 0.298 inches  |
|---|
| Tempurature Rating:   |
| -65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response |
| Outside Diameter:   |
| 0.469 inches  |
| Minimum Inside Bending Radius:  |
| 4.000 inches  |
| Exterior Color:   |
| Natural   |
| Connection Style:   |
| Swivel nut flare 1st end  |
| End Connection Design:  |
| Straight 1st end  |
| Connection Type:  |
| Threaded internal tube 1st end  |
| Burst Test Pressure:  |
| 2400.0 pounds per square inch   |
| Layer Composition And Location:   |
| Outer layer braided corrosion resistant steel wire                                    |
| Maximum Operating Pressure:   |
| 600.0 pounds per square inch  |
| Thread Size:  |
| 0.562 inches 1st end  |
| Seat Angle:   |
| 37.0 degrees 1st end  |
| Hydrostatic Test Pressure:  |
| 1200.0 pounds per square inch   |
| Outer Covering Environmental Protection:  |
| Corrosion resistant   |
| Inside Surface Condition:   |
| Smooth  |
| Measuring Method And Length:  |
| 10.000 inches   |
| Special Features:   |
| Nonconductive virgin materials  |

## NSN 4720-01-123-8830

Nonmetallic Hose Assembly - Page 2 of 2



| Throad  | Carias | Decimates   |
|---------|--------|-------------|
| illieau | oenes  | Designator: |

Unf 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0