NSN 4720-01-124-0279

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-124-0279

| Cross Sectional Shape |
|---|
| Cross Sectional Shape: |
| Round Thread Class |
| Thread Class: |
| 2b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.391 inches |
| Tempurature Rating: |
| -65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.585 inches |
| Minimum Inside Bending Radius: |
| 4.620 inches |
| Connection Style: |
| Swivel nut flare 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Burst Test Pressure: |
| 2400.0 pounds per square inch |
| Layer Composition And Location: |
| Outer layer braided corrosion resistant steel wire |
| Maximum Operating Pressure: |
| 600.0 pounds per square inch |
| Thread Size: |
| 0.750 inches 1st end |
| Seat Angle: |
| 37.0 degrees 1st end |
| Hydrostatic Test Pressure: |
| 1200.0 pounds per square inch |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 120.000 inches |
| Thread Series Designator: |
| Unf 1st end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 4720-01-124-0279

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0