Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-124-4125

Cross S	Sectional	Shape:
---------	-----------	--------

Round

Thread Class:

3b 1st end

# Thread Direction:

Right-hand 1st end

## Inside Diameter:

1.780 inches

#### **Tempurature Rating:**

-65.0 degrees fahrenheit and 300.0 degrees fahrenheit single response

#### **Outside Diameter:**

2.100 inches

Minimum Inside Bending Radius:

12.500 inches

## Connection Style:

Swivel nut flare 2nd end

## End Connection Design:

Straight 1st end

### **Connection Type:**

Threaded internal tube 1st end

## Features Provided:

Internal support

### Thready Qty Per Inch (tpi):

12 2nd end

### **Burst Test Pressure:**

1200.0 pounds per square inch

### Layer Composition And Location:

1st layer braided corrosion resistant steel wire, partial coverage and outer layer braided corrosion resistant steel wire

### Maximum Operating Pressure:

200.0 pounds per square inch

#### **Thread Size:**

2.500 inches 2nd end

#### Seat Angle:

37.0 degrees 2nd end

### Hydrostatic Test Pressure:

600.0 pounds per square inch

#### Flow Angle:

90.0 degrees 2nd end

## Inside Surface Condition:

Smooth

### Measuring Method And Length:

49.005 inches working and 49.995 inches working

Nonmetallic Hose Assembly - Page 2 of 2



Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unj 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0