NSN 4720-01-125-5184

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-125-5184

Cross Sectional Shape: Round Thread Class: 3b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.190 inches Tempurature Rating: -65.0 degrees fahrenheit and 160.0 degrees fahrenheit single response Outside Diameter: 0.410 inches Minimum Inside Bending Radius: 2.000 inches
Thread Class: 3b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.190 inches Tempurature Rating: -65.0 degrees fahrenheit and 160.0 degrees fahrenheit single response Outside Diameter: 0.410 inches Minimum Inside Bending Radius:
3b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.190 inches Tempurature Rating: -65.0 degrees fahrenheit and 160.0 degrees fahrenheit single response Outside Diameter: 0.410 inches Minimum Inside Bending Radius:
Thread Direction: Right-hand 1st end Inside Diameter: 0.190 inches Tempurature Rating: -65.0 degrees fahrenheit and 160.0 degrees fahrenheit single response Outside Diameter: 0.410 inches Minimum Inside Bending Radius:
Right-hand 1st end Inside Diameter: 0.190 inches Tempurature Rating: -65.0 degrees fahrenheit and 160.0 degrees fahrenheit single response Outside Diameter: 0.410 inches Minimum Inside Bending Radius:
Inside Diameter: 0.190 inches Tempurature Rating: -65.0 degrees fahrenheit and 160.0 degrees fahrenheit single response Outside Diameter: 0.410 inches Minimum Inside Bending Radius:
0.190 inches Tempurature Rating: -65.0 degrees fahrenheit and 160.0 degrees fahrenheit single response Outside Diameter: 0.410 inches Minimum Inside Bending Radius:
Tempurature Rating: -65.0 degrees fahrenheit and 160.0 degrees fahrenheit single response Outside Diameter: 0.410 inches Minimum Inside Bending Radius:
-65.0 degrees fahrenheit and 160.0 degrees fahrenheit single response Outside Diameter: 0.410 inches Minimum Inside Bending Radius:
Outside Diameter: 0.410 inches Minimum Inside Bending Radius:
0.410 inches Minimum Inside Bending Radius:
Minimum Inside Bending Radius:
-
2.000 inches
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Layer Composition And Location:
1st layer braided cotton cord and outer layer molded rubber, synthetic
Maximum Operating Pressure:
50.0 pounds per square inch
Thread Size:
0.375 inches 1st end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
500.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:
28.000 inches working
Media For Which Designed:
Air single response
Thread Series Designator:
Unf 2nd end
Shelf Life:

N/a

NSN 4720-01-125-5184

Nonmetallic Hose Assembly - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A542a0