NSN 4720-01-125-5866

Cross Sectional Shape:

Measuring Method And Length: 17.375 inches and 17.875 inches

Round

Thread Class:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-125-5866

3b 1st end				
Thread Direction:				
Right-hand 1st end				
Inside Diameter:				
0.485 inches				
Tempurature Rating:				
-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response				
Outside Diameter:				
0.740 inches				
Minimum Inside Bending Radius:				
3.250 inches				
Exterior Color:				
Clear				
Angle Between Rigid Elbow Fittings In Deg:				
265.0				
Connection Style:				
Swivel nut, flareless 1st end				
End Connection Design:				
Elbow 1st end				
Connection Type:				
Threaded internal tube 1st end				
Burst Test Pressure:				
10000.0 pounds per square inch				
Layer Composition And Location:				
Outer layer braided corrosion resistant steel wire				
Maximum Operating Pressure:				
3000.0 pounds per square inch				
Thread Size:				
0.875 inches 1st end				
Seat Angle:				
12.0 degrees 1st end				
Hydrostatic Test Pressure:				
6000.0 pounds per square inch				
Flow Angle:				
90.0 degrees 1st end				
Inside Surface Condition:				
Smooth				

NSN 4720-01-125-5866

Nonmetallic Hose Assembly - Page 2 of 2



_		•	_	
ı	hread	Series	1)66	ignator:
•	mcaa	OCI ICS	000	igilatoi.

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0