NSN 4720-01-125-9758

Cross Sectional Shape:

Round

Smooth

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-125-9758

Thread Class:
2a 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.420 inches
Tempurature Rating:
-40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response
Outside Diameter:
0.540 inches
Minimum Inside Bending Radius:
5.250 inches
Exterior Color:
Natural
Connection Style:
Swivel nut, inverted flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external tube 1st end
Features Provided:
Reusable end fittings
Thready Qty Per Inch (tpi):
18 1st end
Burst Test Pressure:
6000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.750 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Outer Covering Environmental Protection:
Corrosion resistant
Inside Surface Condition:

NSN 4720-01-125-9758

Nonmetallic Hose Assembly - Page 2 of 2



Measuring	Method	And	Length:

26.500 inches working

Thread Series Designator:

Uns 1st end

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A542a0