

View Online at <https://aerobasegroup.com/nsn/4720-01-126-3546>

Cross Sectional Shape:

Round

Thread Class:

2b and 2a 1st end

Thread Direction:

Right-hand and right-hand 1st end

Inside Diameter:

0.125 inches

Temperature Rating:

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Flange Thickness:

0.458 inches 2nd end

Outside Diameter:

0.430 inches

Minimum Inside Bending Radius:

1.500 inches

Exterior Color:

Black

Connection Style:

Inverted flare 1st end

Bolt Hole Diameter:

0.400 inches 2nd end

End Connection Design:

Straight 2nd end

Connection Type:

Unthreaded fluid passage bolt 2nd end

Burst Test Pressure:

2000.0 pounds per square inch

Layer Composition And Location:

1st layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic

Maximum Operating Pressure:

500.0 pounds per square inch

Thread Size:

0.312 inches and 0.625 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

1000.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

15.250 inches

Media For Which Designed:

Hydraulic fluid single response

Thread Series Designator:

Unf and unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0