Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-126-4860

view Online at https://aerobasegroup.com/nsn/4720-01-126-4860
Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 275.0 degrees fahrenheit single response
Outside Diameter:
0.578 inches
Minimum Inside Bending Radius:
3.380 inches
Exterior Color:
Black
Connection Style:
Swivel nut, inverted flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external tube 1st end
Burst Test Pressure:
10000.0 pounds per square inch
Layer Composition And Location:
1st layer braided fabric and 2nd layer braided wire and outer layer rubber impregnated braided fabric
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.500 inches 1st end
Seat Angle:
30.0 degrees 1st end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
9.000 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Unf 1st end

NSN 4720-01-126-4860

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

