Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-126-7609

C	ross Sectional Shape:
	ound
	hread Class:
	a 1st end
	hread Direction:
	ight-hand 1st end
	nside Diameter:
	300 inches
	empurature Rating:
	5.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response
	utside Diameter:
-	540 inches
	inimum Inside Bending Radius:
	500 inches
	onnection Style:
	wivel nut, inverted flare 2nd end
	nd Connection Design:
	traight 1st end
	onnection Type:
	hreaded external tube 2nd end
В	urst Test Pressure:
	2000.0 pounds per square inch
Μ	aximum Operating Pressure:
30	000.0 pounds per square inch
TI	hread Size:
0.	562 inches 2nd end
S	eat Angle:
37	7.0 degrees 2nd end
FI	low Angle:
90	0.0 degrees 2nd end
In	side Surface Condition:
Sı	mooth
Μ	easuring Method And Length:
12	2.500 inches
TI	hread Series Designator:
U	njf 1st end
S	helf Life:
N	/a
U	nit Of Measure:
D	emilitarization:
N	0

NSN 4720-01-126-7609

Nonmetallic Hose Assembly - Page 2 of 2

Fiig: A542a0

