Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-126-7610

Round         Thread Class:         3a 1st end         Thread Direction:         Right-hand 1st end         Inside Diameter:         0.300 inches         Tempurature Rating:         -650 degrees fahrenheit single response and 400.0 degrees fahrenheit single response         Otside Diameter:         0.540 inches         Minimun Inside Bending Radius:         2.500 inches         End Application:         Aircraft, hunderbolt ii, a-10         Connection Design:         Straight 1st end         Direction Type:         Threaded external hose 2nd end         Burst Test Pressure:         12000.0 pounds per square inch         Miximum Operating Pressure:         0.540 inches Sub         Flow Angle:         0.540 inches Sub end         Herst Test Pressure:         12000.0 pounds per square inch         Miximum Operating Pressure:         0.540 inches Sub end         Flow Angle:         0.540 inches Sub end         Flow Angle:         0.540 inches Condition:         Feat         Inside Surface Condition:         Feat         Miseuring Metod And Lengit:      <		
Thread Class:         3a 1st end         Thread Direction:         Right-hand 1st end         Inside Diameter:         0.300 inches         Tempurature Rating:         e5.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response         Outside Diameter:         0.540 inches         Minimun Inside Bending Radius:         2.500 inches         Aircraft, thunderbolt ii, a-10         Connection Style:         Straight 1st end         Derived external hose 2nd end         Burst Test Pressure:         12000.0 pounds per square inch         Mizerati         3000.0 pounds per square inch         Thread Size:         0.562 inches 2nd end         Flow Angle:         0.500 pounds per square inch         Thread Size:         0.562 inches 2nd end         Flow Angle:         0.562 inches	Cross Sectional Shape:	
A 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.300 inches Tempurature Rating: -55.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response Outside Diameter: 0.540 inches Minimun Inside Bending Radius: 2.500 inches Minimun Inside Bending Radius: 2.500 inches End Application: Aircraft, thunderbolt ii, a-10 Connection Style: Swivel, plain 2nd end End Connection Design: Straight 1st end Connection Type: Threaded external hose 2nd end Burst Test Pressure: 12000.0 pounds per square inch Maximun Operating Pressure: 3000.0 pounds per square inch Freat 11.200.0 pounds per square inch Maximun Operating Pressure: 3000.0 pounds per square inch 3000.0	Round	
Thread Direction:         Right-hand 1st end         Inside Diameter:         0.300 inches         Tempurature Rating:         -65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response         Outside Diameter:         0.540 inches         Minimum Inside Bending Radius:         2.500 inches         End Application:         Aircraft, thunderbolt ii, a-10         Connection Style:         Swivel, plain 2nd end         End Connection Design:         Straight 1st end         Connection Type:         Threaded external hose 2nd end         Burst Test Pressure:         12000.0 pounds per square inch         Maximum Operating Pressure:         0300.0 pounds per square inch         Thread Ext:         0.562 inches 2nd end         Freed         Maximum Operating Pressure:         0300.0 pounds per square inch         Thread Ext:         0.562 inches 2nd end         Freed         Inside Surface Condition:         Feat         Inside Surface Condition:         Feat         Inside Surface Condition:         Smooth         Measuring Method And Lengt	Thread Class:	
Right-hand 1st end         Inside Diameter:         0.300 inches         Tempurature Rating:         -65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response         Outside Diameter:         0.540 inches         Minimum Inside Bending Radius:         2.500 inches         End Application:         Aircraft, thunderbolt ii, a-10         Connection Style:         Swivel, plain 2nd end         Burst Connection Design:         Straight 1st end         Duroution Suple:         12000.0 pounds per square inch         Maximum Operating Pressure:         3000.0 pounds per square inch         Freed Size:         0.562 inches 2nd end         Frew Angle:         9.0.0 degrees 2nd end         Freed Size:         9.0.0 degrees 2nd end         Freat         Inside Surface Condition:         Feat         Inside Surface Condition:         Smooth         Measuring Method And Length:	3a 1st end	
Inside Diameter:         0.300 inches         Fempurature Rating:         -65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response         Dutside Diameter:         0.540 inches         Minimun Inside Bending Radius:         2.500 inches         End Application:         Aircraft, thunderbolt ii, a-10         Connection Style:         Swivel, plain 2nd end         End Connection Design:         Straight 1st end         Dutside external hose 2nd end         Burst Test Pressure:         12000.0 pounds per square inch         Maximum Operating Pressure:         3000.0 pounds per square inch         Firead Size:         0.562 inches 2nd end         Firead Size:         13000.0 pounds per square inch         Firead Size:         0.562 inches 2nd end         Firead Size:         19.0 degrees 2nd end         Firead Size:         19.0 degrees 2nd end         Firead Size:         19.0 degrees 2nd end         Firead         Inside Surface Condition:         Fieat         Inside Surface Condition:         Smooth         Maximy Method And Length:<	Thread Direction:	
0.300 inchesFenpurature Rating:-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single responseOutside Diameter:0.540 inchesMinimun Inside Bending Radius:2.500 inchesEnd Application:Aircraft, thunderbolt ii, a-10Connection Style:Swivel, plain 2nd endEnd Connection Design:Straight 1st endConnection Type:Threaded external hose 2nd endBurst Test Pressure:1000.0 pounds per square inchMaximum Operating Pressure:0.562 inches 2nd endFiread Size:0.0 degrees 2nd endFiread Size:0.0.0 pounds per square inchFiread Size:10.0 degrees 2nd endFiread Size:Firead Size:10.0 degrees 2nd end10.0 degrees 2nd	Right-hand 1st end	
Temperature Rating:         -65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response         Outside Diameter:         0.540 inches         Minimun Inside Bending Radius:         2.500 inches         End Application:         Aircraft, thunderbolt ii, a-10         Connection Style:         Swivel, plain 2nd end         End Connection Design:         Straight 1st end         Connection Type:         Threaded external hose 2nd end         Burst Test Pressure:         12000.0 pounds per square inch         Maximum Operating Pressure:         0.562 inches 2nd end         Firead Size:         0.0.10 degrees 2nd end         Firead Size:         10.0.10 degrees 2nd end         Firead Size:         10.10 degrees 2nd end         Firead         Inside Surface Condition:         Feat         Inside Surface Condition:         Smoth         Measuring Method And Length:         13.125 inches work	Inside Diameter:	
-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response         Outside Diameter:         0.540 inches         Minimun Inside Bending Radius:         2.500 inches         End Application:         Aircraft, thunderbolt ii, a-10         Connection Style:         Swivel, plain 2nd end         End Connection Design:         Straight 1st end         Connection Type:         Threaded external hose 2nd end         Burst Test Pressure:         12000.0 pounds per square inch         Maximum Operating Pressure:         3000.0 pounds per square inch         Flore Angle:         90.0 degrees 2nd end         Flow Angle:         Pasotfication:         Feat         Inside Surface Condition:         Smooth         Mesuring Method And Length:         13.125 inches working	0.300 inches	
Outside Diameter:0.540 inchesMinimum Inside Bending Radius:2.500 inchesEnd Application:Aircraft, thunderbolt ii, a-10Connection Style:Swivel, plain 2nd endEnd Connection Design:Straight 1st endConnection Type:Threaded external hose 2nd endBurst Test Pressure:12000.0 pounds per square inchMaximum Operating Pressure:3000.0 pounds per square inchFlow Angle:90.0 degrees 2nd endFlow Angle:90.0 degrees 2nd endFlow Angle:Straight Code Justification:FeatInside Surface Condition:SmoothMeasuring Method And Length:13.125 inches working	Tempurature Rating:	
0.540 inches Minimun Inside Bending Radius: 2.500 inches End Application: Aircraft, thunderbolt ii, a-10 Connection Style: Swivel, plain 2nd end End Connection Design: Straight 1st end Connection Type: Threaded external hose 2nd end Burst Test Pressure: 12000.0 pounds per square inch Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.562 inches 2nd end Flow Angle: 9.0 degrees 2nd end Criticality Code Justification: Feat Inside Surface Condition: Smoth Measuring Method And Length: 13.125 inches working	-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response	
Minimum Inside Bending Radius: 2.500 inches End Application: Aircraft, thunderbolt ii, a-10 Connection Style: Swivel, plain 2nd end End Connection Design: Straight 1st end Connection Type: Threaded external hose 2nd end Burst Test Pressure: 12000.0 pounds per square inch Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.562 inches 2nd end Elow Angle: 90.0 degrees 2nd end For Angle: 90.0 degrees 2nd end Environment of the stratement of t	Outside Diameter:	
2.500 inchesEnd Application:Aircraft, thunderbolt ii, a-10Connection Style:Swivel, plain 2nd endEnd Connection Design:Straight 1st endConnection Type:Threaded external hose 2nd endBurst Test Pressure:12000.0 pounds per square inchMaximum Operating Pressure:3000.0 pounds per square inchFhread Size:0.562 inches 2nd endFlow Angle:90.0 degrees 2nd endFlow Angle:90.0 degrees 2nd endSitticality Code Justification:FeatInside Surface Condition:SmoothMeasuring Method And Length:13.125 inches working	0.540 inches	
End Application:   Aircraft, thunderbolt ii, a-10   Connection Style:   Swivel, plain 2nd end   End Connection Design:   Straight 1st end   Connection Type:   Threaded external hose 2nd end   Burst Test Pressure:   12000.0 pounds per square inch   Maximum Operating Pressure:   3000.0 pounds per square inch   Fhread Size:   0.562 inches 2nd end   Flow Angle:   90.0 degrees 2nd end   Criticality Code Justification:   Feat   Inside Surface Condition:   Smooth   Measuring Method And Length:   13.125 inches working	Minimum Inside Bending Radius:	
Aircraft, thunderbolt ii, a-10 Connection Style: Swivel, plain 2nd end End Connection Design: Straight 1st end Connection Type: Threaded external hose 2nd end Burst Test Pressure: 12000.0 pounds per square inch Maximum Operating Pressure: 3000.0 pounds per square inch Maximum Operating Pressure: 3000.0 pounds per square inch Maximum Operating Pressure: 3000.0 pounds per square inch Firead Size: 0.562 inches 2nd end Fiow Angle: 90.0 degrees 2nd end Criticality Code Justification: Feat Inside Surface Condition: Smooth Measuring Method And Length: 13.125 inches working	2.500 inches	
Connection Style:Swivel, plain 2nd endEnd Connection Design:Straight 1st endConnection Type:Threaded external hose 2nd endBurst Test Pressure:12000.0 pounds per square inchMaximum Operating Pressure:3000.0 pounds per square inchThread Size:0.562 inches 2nd endFlow Angle:90.0 degrees 2nd endCriticality Code Justification:FeatInside Surface Condition:SmoothMeasuring Method And Length:13.125 inches working	End Application:	
Swivel, plain 2nd end End Connection Design: Straight 1st end Connection Type: Threaded external hose 2nd end Burst Test Pressure: 12000.0 pounds per square inch Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.562 inches 2nd end Flow Angle: 90.0 degrees 2nd end Criticality Code Justification: Feat Inside Surface Condition: Smooth Measuring Method And Length: 13.125 inches working	Aircraft, thunderbolt ii, a-10	
End Connection Design:Straight 1st endConnection Type:Threaded external hose 2nd endBurst Test Pressure:12000.0 pounds per square inchMaximum Operating Pressure:3000.0 pounds per square inchThread Size:0.562 inches 2nd endFlow Angle:90.0 degrees 2nd endFreatInside Surface Condition:SmoothMasuring Method And Length:13.125 inches working	Connection Style:	
Straight 1st end Connection Type: Threaded external hose 2nd end Burst Test Pressure: 12000.0 pounds per square inch Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.562 inches 2nd end Flow Angle: 90.0 degrees 2nd end Criticality Code Justification: Feat Inside Surface Condition: Smooth Measuring Method And Length: 13.125 inches working	Swivel, plain 2nd end	
Connection Type:Threaded external hose 2nd endBurst Test Pressure:12000.0 pounds per square inchMaximum Operating Pressure:3000.0 pounds per square inchThread Size:0.562 inches 2nd endFlow Angle:90.0 degrees 2nd endCriticality Code Justification:FeatInside Surface Condition:SmoothMeasuring Method And Length:13.125 inches working	End Connection Design:	
Threaded external hose 2nd end Burst Test Pressure: 12000.0 pounds per square inch Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.562 inches 2nd end Flow Angle: 90.0 degrees 2nd end Criticality Code Justification: Feat Inside Surface Condition: Smooth Measuring Method And Length: 13.125 inches working	Straight 1st end	
Burst Test Pressure:12000.0 pounds per square inchMaximum Operating Pressure:3000.0 pounds per square inchThread Size:0.562 inches 2nd endFlow Angle:90.0 degrees 2nd endCriticality Code Justification:FeatInside Surface Condition:SmoothMeasuring Method And Length:13.125 inches working	Connection Type:	
12000.0 pounds per square inch Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.562 inches 2nd end Flow Angle: 90.0 degrees 2nd end Criticality Code Justification: Feat Inside Surface Condition: Smooth Measuring Method And Length: 13.125 inches working	Threaded external hose 2nd end	
Maximum Operating Pressure:3000.0 pounds per square inchThread Size:0.562 inches 2nd endFlow Angle:90.0 degrees 2nd endCriticality Code Justification:FeatInside Surface Condition:SmoothMeasuring Method And Length:13.125 inches working	Burst Test Pressure:	
3000.0 pounds per square inch Thread Size: 0.562 inches 2nd end Flow Angle: 90.0 degrees 2nd end Criticality Code Justification: Feat Inside Surface Condition: Smooth Measuring Method And Length: 13.125 inches working	12000.0 pounds per square inch	
Thread Size:0.562 inches 2nd endFlow Angle:90.0 degrees 2nd endCriticality Code Justification:FeatInside Surface Condition:SmoothMeasuring Method And Length:13.125 inches working	Maximum Operating Pressure:	
0.562 inches 2nd end Flow Angle: 90.0 degrees 2nd end Criticality Code Justification: Feat Inside Surface Condition: Smooth Measuring Method And Length: 13.125 inches working	3000.0 pounds per square inch	
Flow Angle:90.0 degrees 2nd endCriticality Code Justification:FeatInside Surface Condition:SmoothMeasuring Method And Length:13.125 inches working	Thread Size:	
90.0 degrees 2nd end Criticality Code Justification: Feat Inside Surface Condition: Smooth Measuring Method And Length: 13.125 inches working	0.562 inches 2nd end	
Criticality Code Justification: Feat Inside Surface Condition: Smooth Measuring Method And Length: 13.125 inches working	Flow Angle:	
Feat Inside Surface Condition: Smooth Measuring Method And Length: 13.125 inches working	90.0 degrees 2nd end	
Inside Surface Condition: Smooth Measuring Method And Length: 13.125 inches working	Criticality Code Justification:	
Smooth Measuring Method And Length: 13.125 inches working	Feat	
Measuring Method And Length: 13.125 inches working	Inside Surface Condition:	
13.125 inches working	Smooth	
	Measuring Method And Length:	
Special Features:	13.125 inches working	
	Special Features:	
Weapon system essential	Weapon system essential	
Thread Series Designator:	Thread Series Designator:	
Unjf 1st end	Unjf 1st end	
Shelf Life:	Shelf Life:	
N/a	N/a	

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0