Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-126-9174

Cross Sectional Shape	2
Round	

Thread Class:

3b 1st end

## **Thread Direction:**

Right-hand 1st end

## Inside Diameter:

0.375 inches

#### **Tempurature Rating:**

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

### **Outside Diameter:**

0.688 inches

Minimum Inside Bending Radius:

#### 5.000 inches

**Exterior Color:** 

Black

### **Connection Style:**

Swivel nut flare 1st end

#### **End Connection Design:**

Straight 2nd end

## **Connection Type:**

Threaded internal tube 1st end

### Features Provided:

Nonskive

### **Burst Test Pressure:**

9000.0 pounds per square inch

### Layer Composition And Location:

1st layer braided steel wire and outer layer molded rubber, synthetic

### Maximum Operating Pressure:

2250.0 pounds per square inch

#### Thread Size:

0.562 inches 1st end

#### Seat Angle:

37.0 degrees 1st end

#### Hydrostatic Test Pressure:

4500.0 pounds per square inch

## **Outer Covering Environmental Protection:**

Oil resistant and weatherproof

## Inside Surface Condition:

Smooth

# Measuring Method And Length:

60.000 inches



Media For Which Designed:

Fuel/oil, hydrocarbon single response

## Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No

Fiig:

A542a0