Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-128-4586

Cross Sectional Shape:	
Round	
hread Class:	
b 1st end	
hread Direction:	
light-hand 1st end	
nside Diameter:	
.880 inches	
empurature Rating:	
40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response	
Dutside Diameter:	
.220 inches	
Inimum Inside Bending Radius:	
.250 inches	
Connection Style:	
Swivel nut flare 1st end	
Ind Connection Design:	
straight 1st end	
Connection Type:	
hreaded internal tube 1st end	
hready Qty Per Inch (tpi):	
2 1st end	
Burst Test Pressure:	
800.0 pounds per square inch	
ayer Composition And Location:	
st layer braided textile yarn and 2nd layer braided corrosion resistant steel wire and outer layer rubber impregnated braided	fabric
faximum Operating Pressure:	
50.0 pounds per square inch	
hread Size:	
.312 inches 1st end	
eat Angle:	
7.0 degrees 1st end	
nside Surface Condition:	
Smooth	
leasuring Method And Length:	
1.000 inches	
ledia For Which Designed:	
ir and fuel/oil, hydrocarbon and water single response	
hread Series Designator:	
In 1st end	
shelf Life:	
l/a	

NSN 4720-01-128-4586

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0