NSN 4720-01-128-6779

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-128-6779

| Cross Sectional Shape: |
|---|
| Round |
| Thread Class: |
| 3b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.415 inches |
| Tempurature Rating: |
| -65.0 degrees fahrenheit single response and 300.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.672 inches |
| Minimum Inside Bending Radius: |
| 3.500 inches |
| Connection Style: |
| Nut assembly with gasket 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded internal hose 1st end |
| Features Provided: |
| Reusable end fittings |
| Burst Test Pressure: |
| 5000.0 pounds per square inch |
| Maximum Operating Pressure: |
| 1000.0 pounds per square inch |
| Thread Size: |
| 0.750 inches 1st end |
| Hydrostatic Test Pressure: |
| 2500.0 pounds per square inch |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 5.500 inches working |
| Media For Which Designed: |
| Fuel/oil, hydrocarbon single response |
| Thread Series Designator: |
| Unjf 1st end |
| Specification Data: |
| 81349-mil-h-83796/1 government specification |
| Shelf Life: |
| N/a |

NSN 4720-01-128-6779

Nonmetallic Hose Assembly - Page 2 of 2



| ı | In | it I | Of | · M | دما | e i | ıre: |
|---|----|------|----|-----|-----|-----|------|
| ι | JΝ | II ' | ωı | IV | еа | SU | ıre: |

--

Demilitarization:

No

Fiig:

A542a0