Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-129-6081

view Online at https://aeiobasegroup.com/hsi//4720-01-129-0001	
Cross Sectional Shape:	
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
1.375 inches	
Tempurature Rating:	
-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response	
Outside Diameter:	
1.704 inches	
Minimum Inside Bending Radius:	
6.000 inches	
Connection Style:	
Swivel nut flare 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Burst Test Pressure:	
2000.0 pounds per square inch	
Layer Composition And Location:	
1st layer braided corrosion resistant steel wire, partial coverage and outer layer braided corrosion resistant steel wire	
Maximum Operating Pressure:	
250.0 pounds per square inch	
Thread Size:	
1.875 inches 1st end	
Seat Angle:	
37.0 degrees 1st end	
Hydrostatic Test Pressure:	
800.0 pounds per square inch	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
49.750 inches	
Media For Which Designed:	
Fuel/oil, hydrocarbon single response	
Thread Series Designator:	
Unjf 1st end	
Shelf Life:	
N/a	

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0