

View Online at <https://aerobasegroup.com/nsn/4720-01-130-4360>

**Cross Sectional Shape:**

Round

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.375 inches

**Temperature Rating:**

-65.0 degrees fahrenheit single response and 212.0 degrees fahrenheit single response

**Outside Diameter:**

0.750 inches

**Minimum Inside Bending Radius:**

3.750 inches

**Exterior Color:**

Black

**Connection Style:**

Swivel, plain 2nd end

**End Connection Design:**

Straight 2nd end

**End Fitting Component And Material:**

Complete fitting steel all ends

**Fitting Component And Surface Treatment:**

Complete fitting dichromate 1st end

**Connection Type:**

Threaded external pipe 2nd end

**Second End Relationship With First End:**

Not identical

**Burst Test Pressure:**

900.0 pounds per square inch

**First End Swivel Action Capability:**

Not included

**Layer Composition And Location:**

2nd layer molded rubber, chloroprene err-100

**Maximum Operating Pressure:**

225.0 pounds per square inch

**Thread Size:**

0.375 inches 1st end

**Hydrostatic Test Pressure:**

450.0 pounds per square inch

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

19.000 inches

**Second End Swivel Action Capability:**

Not included

**Special Features:**

Inner conveying tube material-rubber, synthetic

**Media For Which Designed:**

Air single response

**Thread Series Designator:**

Nptf 2nd end

**Specification Data:**

81349-mil-h-3992 government specification

**Specification Or Standard:**

1 type and 1 class or 2 class

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0

**Mil-std (military Standard):**

Mil-h-3992 spec.