## NSN 4720-01-130-5466



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-01-130-5466 **Cross Sectional Shape:** Round **Thread Class:** 3a 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.375 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.610 inches **Minimum Inside Bending Radius:** 3.000 inches **Connection Style:** Swivel nut, inverted flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded external tube 1st end **Burst Test Pressure:** 1000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided fabric and outer layer rubber impregnated braided fabric **Maximum Operating Pressure:** 250.0 pounds per square inch **Thread Size:** 0.625 inches 1st end Seat Angle: 45.0 degrees 1st end **Inside Surface Condition: Measuring Method And Length:** 34.000 inches Media For Which Designed: Air and fuel/oil, hydrocarbon and water single response **Thread Series Designator:** Unf 1st end

Shelf Life: N/a Unit Of Measure: --

## NSN 4720-01-130-5466

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0