NSN 4720-01-131-0248

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-131-0248

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.313 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
0.672 inches
Minimum Inside Bending Radius:
4.000 inches
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
12000.0 pounds per square inch
Layer Composition And Location:
1st layer braided fabric and 2nd layer braided wire and outer layer rubber impregnated braided fabric
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.562 inches 2nd end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Flow Angle:
45.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:
10.438 inches working
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:

Unjf 1st end

NSN 4720-01-131-0248

Nonmetallic Hose Assembly - Page 2 of 2



				-
C I	20	lŧ.	l i	fe:
J.	16		_,	ıc.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0