Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-131-0671

| Cross Sectional Shape: |
|---|
| Round |
| Thread Class: |
| 3b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.415 inches |
| Tempurature Rating: |
| -65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.500 inches |
| Minimum Inside Bending Radius: |
| 3.500 inches |
| Inner Conveying Tube Material: |
| Elastomer |
| Connection Style: |
| Swivel nut flare 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Features Provided: |
| Reusable end fittings |
| Second End Relationship With First End: |
| Identical |
| Burst Test Pressure: |
| 5000.0 pounds per square inch |
| First End Swivel Action Capability: |
| Included |
| Maximum Operating Pressure: |
| 1000.0 pounds per square inch |
| Thread Size: |
| 0.750 inches 1st end |
| Seat Angle: |
| 37.0 degrees 1st end |
| Hydrostatic Test Pressure: |
| 2500.0 pounds per square inch |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 10.000 inches working |
| |

Nonmetallic Hose Assembly - Page 2 of 2



Special Features:

Inner conveying tube material-elastomer

Media For Which Designed:

Ethylene glycol single response and water single response

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0