## NSN 4720-01-132-4859

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-132-4859

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.500 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
2.050 inches
Minimum Inside Bending Radius:
20.000 inches
Exterior Color:
Black
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Threaded internal tube 1st end Thready Qty Per Inch (tpi):
Thready Qty Per Inch (tpi):
Thready Qty Per Inch (tpi): 12 2nd end
Thready Qty Per Inch (tpi): 12 2nd end Burst Test Pressure:
Thready Qty Per Inch (tpi): 12 2nd end Burst Test Pressure: 2000.0 pounds per square inch
Thready Qty Per Inch (tpi): 12 2nd end Burst Test Pressure: 2000.0 pounds per square inch Layer Composition And Location:
Thready Qty Per Inch (tpi): 12 2nd end Burst Test Pressure: 2000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer spirally wrapped rubber fabric
Thready Qty Per Inch (tpi): 12 2nd end Burst Test Pressure: 2000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer spirally wrapped rubber fabric Maximum Operating Pressure:
Thready Qty Per Inch (tpi):  12 2nd end  Burst Test Pressure:  2000.0 pounds per square inch  Layer Composition And Location:  1st layer braided steel wire and outer layer spirally wrapped rubber fabric  Maximum Operating Pressure:  500.0 pounds per square inch
Thready Qty Per Inch (tpi):  12 2nd end  Burst Test Pressure:  2000.0 pounds per square inch  Layer Composition And Location:  1st layer braided steel wire and outer layer spirally wrapped rubber fabric  Maximum Operating Pressure:  500.0 pounds per square inch  Thread Size:
Thready Qty Per Inch (tpi):  12 2nd end  Burst Test Pressure:  2000.0 pounds per square inch  Layer Composition And Location:  1st layer braided steel wire and outer layer spirally wrapped rubber fabric  Maximum Operating Pressure:  500.0 pounds per square inch  Thread Size:  1.875 inches 2nd end
Thready Qty Per Inch (tpi):  12 2nd end  Burst Test Pressure:  2000.0 pounds per square inch  Layer Composition And Location:  1st layer braided steel wire and outer layer spirally wrapped rubber fabric  Maximum Operating Pressure:  500.0 pounds per square inch  Thread Size:  1.875 inches 2nd end  Seat Angle:
Thready Qty Per Inch (tpi): 12 2nd end Burst Test Pressure: 2000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer spirally wrapped rubber fabric Maximum Operating Pressure: 500.0 pounds per square inch Thread Size: 1.875 inches 2nd end Seat Angle: 37.0 degrees 2nd end
Thready Qty Per Inch (tpi):  12 2nd end  Burst Test Pressure:  2000.0 pounds per square inch  Layer Composition And Location:  1st layer braided steel wire and outer layer spirally wrapped rubber fabric  Maximum Operating Pressure:  500.0 pounds per square inch  Thread Size:  1.875 inches 2nd end  Seat Angle:  37.0 degrees 2nd end  Hydrostatic Test Pressure:
Thready Qty Per Inch (tpi): 12 2nd end Burst Test Pressure: 2000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer spirally wrapped rubber fabric Maximum Operating Pressure: 500.0 pounds per square inch Thread Size: 1.875 inches 2nd end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 1000.0 pounds per square inch
Thready Qty Per Inch (tpi): 12 2nd end  Burst Test Pressure: 2000.0 pounds per square inch  Layer Composition And Location: 1st layer braided steel wire and outer layer spirally wrapped rubber fabric  Maximum Operating Pressure: 500.0 pounds per square inch  Thread Size: 1.875 inches 2nd end  Seat Angle: 37.0 degrees 2nd end  Hydrostatic Test Pressure: 1000.0 pounds per square inch  Outer Covering Environmental Protection:

31.000 inches

**Measuring Method And Length:** 

## NSN 4720-01-132-4859

Nonmetallic Hose Assembly - Page 2 of 2



	•		
I hread	Series	Designator:	

Un 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0