NSN 4720-01-133-4033

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-133-4033

| Cross Sectional Shape: |
|---|
| Round |
| Thread Class: |
| 3b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.875 inches |
| Tempurature Rating: |
| 300.0 degrees fahrenheit single response |
| Outside Diameter: |
| 1.110 inches |
| Minimum Inside Bending Radius: |
| 7.380 inches |
| Connection Style: |
| Swivel nut flare 2nd end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Features Provided: |
| Reusable end fittings |
| Burst Test Pressure: |
| 5000.0 pounds per square inch |
| Layer Composition And Location: |
| 1st layer braided steel wire and outer layer braided steel wire |
| Maximum Operating Pressure: |
| 1250.0 pounds per square inch |
| Thread Size: |
| 1.312 inches 2nd end |
| Seat Angle: |
| 37.0 degrees 2nd end |
| Hydrostatic Test Pressure: |
| 2000.0 pounds per square inch |
| Flow Angle: |
| 45.0 degrees 2nd end |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 11.875 inches |
| Supplementary Features: |

Suppgthis item has been reviewed for asbestos material. The current approved sources (rnvc 2) have indicated their part numbers contained

asbestos. They continue to manufacture the same part number without asbestos material.

NSN 4720-01-133-4033

Nonmetallic Hose Assembly - Page 2 of 2



| Th | road | Series | Docin | nator: |
|----|------|--------|-------|--------|
| ιn | reau | Series | Desig | mator: |

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0