

View Online at <https://aerobasegroup.com/nsn/4720-01-133-5954>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

1.130 inches

Temperature Rating:

-65.0 degrees fahrenheit and 450.0 degrees fahrenheit single response

Outside Diameter:

1.360 inches

Minimum Inside Bending Radius:

11.000 inches

Angle Between Rigid Elbow Fittings In Deg:

119.0

Connection Style:

Swivel nut flare 2nd end

End Connection Design:

Elbow 2nd end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

12 2nd end

Burst Test Pressure:

4000.0 pounds per square inch

Layer Composition And Location:

1st layer braided steel wire and outer layer braided steel wire

Maximum Operating Pressure:

1000.0 pounds per square inch

Thread Size:

1.625 inches 2nd end

Seat Angle:

37.0 degrees 2nd end

Hydrostatic Test Pressure:

2000.0 pounds per square inch

Flow Angle:

82.0 degrees 2nd end

Inside Surface Condition:

Smooth

Measuring Method And Length:

11.270 inches working

Supplementary Features:

This item has been reviewed for asbestos material. The current approved sources (rnc) have indicated their part numbers contained asbestos. They continue to manufacture the same part number without asbestos material.

Thread Series Designator:

Unj 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A542a0