Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-134-3479

Cross Sectional Shape:
Round
Thread Class:
1a 2nd end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 275.0 degrees fahrenheit single response
Outside Diameter:
0.650 inches
Minimum Inside Bending Radius:
5.000 inches
Exterior Color:
Green
Connection Style:
Inverted flare 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded external pipe 1st end
Thready Qty Per Inch (tpi):
16 2nd end
Burst Test Pressure:
20000.0 pounds per square inch
Layer Composition And Location:
1st layer braided rayon cord and 2nd layer braided rayon cord and outer layer molded rubber, synthetic
Maximum Operating Pressure:
10000.0 pounds per square inch
Thread Size:
1.125 inches 2nd end
Seat Angle:
30.0 degrees 1st end
Hydrostatic Test Pressure:
15000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
290.000 inches
Special Features:
Second end furnished w/self sealing feature and dust cap and chain

Nonmetallic Hose Assembly - Page 2 of 2



## Media For Which Designed:

Fuel/oil, hydrocarbon and water and air and alcohol, methyl single response

## Thread Series Designator:

Un 2nd end

Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A542a0