Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-134-3578

Cr	oss Sectional Shape:
Ro	bund
Th	iread Class:
3b	1st end
Th	read Direction:
Ri	ght-hand 1st end
Ins	side Diameter:
0.1	188 inches
Те	empurature Rating:
-65	5.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Οι	utside Diameter:
0.3	312 inches
Mi	nimum Inside Bending Radius:
2.0	000 inches
Co	onnection Style:
S٧	vivel nut flare 2nd end
En	nd Connection Design:
Str	raight 1st end
Co	onnection Type:
Th	readed internal tube 1st end
Βu	urst Test Pressure:
70	00.0 pounds per square inch
La	yer Composition And Location:
Οι	uter layer braided corrosion resistant steel wire
Ma	aximum Operating Pressure:
15	00.0 pounds per square inch
Th	iread Size:
0.4	438 inches 1st end
Se	eat Angle:
37	.0 degrees 2nd end
Hy	vdrostatic Test Pressure:
30	00.0 pounds per square inch
Flo	ow Angle:
45	.0 degrees 2nd end
Ins	side Surface Condition:
Sn	nooth
Me	easuring Method And Length:
6.7	750 inches working
Th	read Series Designator:
Un	njf 1st end
Sh	nelf Life:
N/a	a

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0