Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-134-3582

v	/iew Online at https://aerobasegroup.com/nsn/4720-01-134-3582
С	cross Sectional Shape:
R	Round
т	hread Class:
3	b 2nd end
т	hread Direction:
R	light-hand 2nd end
lr	nside Diameter:
0	.625 inches
Т	empurature Rating:
-6	65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single respons
0	Outside Diameter:
0	.789 inches
N	Iinimum Inside Bending Radius:
6	.500 inches
A	ngle Between Rigid Elbow Fittings In Deg:
0	.0
С	Connection Style:
S	wivel nut flare 2nd end
E	nd Connection Design:
E	lbow 2nd end
С	Connection Type:
Т	hreaded internal tube 2nd end
В	Burst Test Pressure:
5	000.0 pounds per square inch
L	ayer Composition And Location:
С	Outer layer braided corrosion resistant steel wire
N	laximum Operating Pressure:
1	000.0 pounds per square inch
т	hread Size:
1	.062 inches 2nd end
S	eat Angle:
3	7.0 degrees 1st end
Н	lydrostatic Test Pressure:
2	000.0 pounds per square inch
F	low Angle:
9	0.0 degrees 2nd end
lr	nside Surface Condition:
S	Smooth
N	leasuring Method And Length:
5	6.000 inches
т	hread Series Designator:
L	Jnf 2nd end

Nonmetallic Hose Assembly - Page 2 of 2

Specification Data:

96906-ms8005 government standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0

