NSN 4720-01-134-3587

Cross Sectional Shape:

400.0 pounds per square inch

Round

Thread Class:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-134-3587

| 3b 1st end |
|--|
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.500 inches |
| Tempurature Rating: |
| 35.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.880 inches |
| Minimum Inside Bending Radius: |
| 5.000 inches |
| Exterior Color: |
| Green |
| Connection Style: |
| Swivel nut flare 1st end |
| End Connection Design: |
| Straight 1st end |
| End Fitting Component And Material: |
| Complete fitting stainless steel all ends |
| Fitting Component And Surface Treatment: |
| Complete fitting passivate 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Second End Relationship With First End: |
| Identical |
| Burst Test Pressure: |
| 800.0 pounds per square inch |
| First End Swivel Action Capability: |
| Not included |
| Layer Composition And Location: |
| Outer layer rubber, grade 149fs75, b f goodrich err-100 |
| Maximum Operating Pressure: |
| 200.0 pounds per square inch |
| Thread Size: |
| 0.750 inches 1st end |
| Seat Angle: |
| 37.0 degrees 1st end |
| Hydroctatic Test Pressure: |

NSN 4720-01-134-3587

Nonmetallic Hose Assembly - Page 2 of 2



| Inside Surface Condition: |
|------------------------------------|
| Smooth |
| Measuring Method And Length |
| 48.000 inches working |
| Thread Series Designator: |
| Unjf 1st end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A542a0