## NSN 4720-01-134-7003

**Cross Sectional Shape:** 

Round

Thread Class: 3b 1st end

Thread Direction: Right-hand 1st end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-134-7003

Inside Diameter:
0.406 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
0.562 inches
Minimum Inside Bending Radius:
4.625 inches
Angle Between Rigid Elbow Fittings In Deg:
261.0
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Elbow 2nd end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
6000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.750 inches 2nd end
0.700 mones and one
Seat Angle:
Seat Angle:
Seat Angle: 37.0 degrees 2nd end
Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure:
Seat Angle: 37.0 degrees 2nd end  Hydrostatic Test Pressure: 3000.0 pounds per square inch
Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Flow Angle:
Seat Angle: 37.0 degrees 2nd end  Hydrostatic Test Pressure: 3000.0 pounds per square inch  Flow Angle: 90.0 degrees 2nd end
Seat Angle: 37.0 degrees 2nd end  Hydrostatic Test Pressure: 3000.0 pounds per square inch  Flow Angle: 90.0 degrees 2nd end Inside Surface Condition:

## NSN 4720-01-134-7003

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:
Unjf 1st end
Specification Data:
96906-ms8005 government standard
Shelf Life:
N/a

Demilitarization:

**Unit Of Measure:** 

No

Fiig:

A542a0