

View Online at <https://aerobasegroup.com/nsn/4720-01-134-7315>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

2.000 inches

**Tempurature Rating:**

32.0 degrees celsius single response and 52.0 degrees celsius single response

**Outside Diameter:**

2.656 inches

**Exterior Color:**

Black

**Hose Or Tubing Specification/std Data:**

Mil-prf-53063b specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**First End Fitting Specification/std Data:**

Ms27025-11 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Second End Fitting Specification/std Data:**

Ms27021-11 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Quick Disconnect Size:**

2.000 inches 2nd end

**Connection Style:**

Cam or lever (external) 2nd end

**End Connection Design:**

Straight 2nd end

**End Fitting Component And Material:**

Complete fitting aluminum alloy all ends

**Connection Type:**

Internal quick disconnect 1st end

**Features Provided:**

Electrostatic discharge capability

**Second End Relationship With First End:**

Not identical

**Burst Test Pressure:**

300.0 pounds per square inch

**First End Swivel Action Capability:**

Not included

**Layer Composition And Location:**

1st layer rubber impregnated braided cotton cord err-100

**Maximum Operating Pressure:**

75.0 pounds per square inch

**Hydrostatic Test Pressure:**

200.0 pounds per square inch

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

60.000 inches excluding end fittings

**Second End Swivel Action Capability:**

Not included

**Special Features:**

Inner conveying tube material-rubber, synthetic

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Specification Data:**

81343-mil-370 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0

**Mil-std (military Standard):**

Mil-prf-53063b spec.