Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-134-8308

Cross Sectional S	hape:
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.500 inches	
Tempurature Rati	ıg:
-55.0 degrees fahre	nheit single response and 300.0 degrees fahrenheit single response
Outside Diameter	
0.828 inches	
Minimum Inside B	ending Radius:
5.500 inches	
End Application:	
2350-01-091-5405	carrier, cargo
Connection Style:	
Swivel nut flare 1st	end
End Connection D	esign:
Straight 1st end	
Connection Type:	
Threaded internal t	ube 1st end
Burst Test Pressu	re:
3500.0 pounds per	square inch
Maximum Operati	ng Pressure:
875.0 pounds per s	quare inch
Thread Size:	
0.875 inches 1st er	d
Seat Angle:	
37.0 degrees 1st e	d
Inside Surface Co	ndition:
Smooth	
Special Features:	
Assembly with add	tional fittings-2-adapter-p/n ms51500b10, 1-coupler body p/n 12300453-7, 1-coupler nose p/n 12300453-8
Thread Series Des	ignator:
Unf 1st end	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	

NSN 4720-01-134-8308

Nonmetallic Hose Assembly - Page 2 of 2

Fiig: A542a0

