NSN 4720-01-134-9830



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-01-134-9830 **Cross Sectional Shape:** Round **Thread Class:** 2a 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.500 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.820 inches **Minimum Inside Bending Radius:** 7.000 inches **Exterior Color:** Black **Connection Style:** Swivel nut, inverted flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded external tube 1st end Thready Qty Per Inch (tpi): 18 1st end **Burst Test Pressure:** 8000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided steel wire and outer layer molded rubber, synthetic **Maximum Operating Pressure:** 2000.0 pounds per square inch **Thread Size:** 0.750 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 4000.0 pounds per square inch **Inside Surface Condition:** Smooth

Measuring Method And Length:

31.500 inches

Media For Which Designed:

Fuel/oil, hydrocarbon single response

NSN 4720-01-134-9830

Nonmetallic Hose Assembly - Page 2 of 2



Thread S	Series	Designator:
----------	--------	-------------

Uns 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0