## NSN 4720-01-135-2955



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-01-135-2955 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.500 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 160.0 degrees fahrenheit single response **Outside Diameter:** 0.750 inches **Minimum Inside Bending Radius:** 6.000 inches **Exterior Color:** Black **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Features Provided:** Reusable end fittings **Burst Test Pressure:** 750.0 pounds per square inch **Layer Composition And Location:** 1st layer braided cotton cord and outer layer molded rubber, synthetic **Maximum Operating Pressure:** 150.0 pounds per square inch

**Thread Size:** 

0.750 inches 1st end

Seat Angle:

37.0 degrees 1st end

**Hydrostatic Test Pressure:** 

300.0 pounds per square inch

**Inside Surface Condition:** 

Smooth

**Measuring Method And Length:** 

360.000 inches

Media For Which Designed:

Fuel/oil, hydrocarbon single response

## NSN 4720-01-135-2955

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:
Unf 1st end
Specification Data:
88044-an6270 government standard
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0