NSN 4720-01-136-0353

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-136-0353

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
nside Diameter:
0.235 inches
Tempurature Rating:
65.0 degrees fahrenheit and 450.0 degrees fahrenheit single response
Outside Diameter:
0.406 inches
Minimum Inside Bending Radius:
2.000 inches
Exterior Color:
Black
Connection Style:
Swivel nut, flareless 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
10000.0 pounds per square inch
Layer Composition And Location:
1st layer braided corrosion resistant steel wire and outer layer molded rubber, neoprene
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.500 inches 1st end
Seat Angle:
12.0 degrees 1st end
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Outer Covering Environmental Protection:
Alcohol resistant and fuel resistant and hydraulic solution resistant and solvent resistant and waterproof and ester resistant and heat
resistant
nside Surface Condition:
Smooth
Measuring Method And Length:
21.380 inches

Special Features:

Permanent identification tag attached; protective closures supplied

NSN 4720-01-136-0353

Nonmetallic Hose Assembly - Page 2 of 2



Thread	Series	Design	nator:
	0000	_00.9.	

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0