NSN 4720-01-136-0359

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-136-0359

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.229 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 400.0 degrees fahrenheit single response
Outside Diameter:
0.420 inches
Minimum Inside Bending Radius:
3.000 inches
Exterior Color:
Black
Connection Style:
Swivel nut, flareless 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
12000.0 pounds per square inch
Layer Composition And Location:
1st layer braided steel wire and 2nd layer molded polytetrafluoroethylene and outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
12.0 degrees 1st end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Outer Covering Environmental Protection:
Alcohol resistant and fuel resistant and hydraulic solution resistant and solvent resistant and waterproof and ester resistant and heat
resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
24.625 inches
Special Features:

Permanent identification tag attached

NSN 4720-01-136-0359

Nonmetallic Hose Assembly - Page 2 of 2



Thread S	Series	Designator:
----------	--------	-------------

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0